

ÖZELLİKLER	BİRİM	SABİT SANTRALLER							MOBİL SANTRALLER				
		EKO-15	EKO-35	EKO-60	SUPER-S 100	GİGA 100	MAXI 130	TERA 180	EKOMOBİL 35	EKOMOBİL 60	SUPERMOBİL 100	GİGAMOBİL 100	MAXIMOBİL 120
SANTRAL KAPASİTESİ													
SIKIŞTIRILMIŞ BETON	m ³ /hr	15	35	60	105	105	130	180	35	60	100	100	120
KARIŞIM ZAMANI	cycle/hr	60	60	60	50	50	45	40	60	60	50	50	45
MİKSER ÖZELLİKLERİ													
MİKSER KAPASİTE	m ³	0,25	0,5	1	2	2	3	4,5	0,5	1	2	2	3
KURU HACİM	lt	350	750	1500	3000	3000	4500	6750	750	1500	3000	3000	4500
SIKIŞTIRILMIŞ BETON	lt	250	500	1000	2000	2000	3000	4500	500	1000	2000	2000	3000
MOTOR GÜCÜ	kW	7,5	18,5	37	2x37	2x37	2x55	2x90	18,5	37	2x37	2x37	2x55
					74	74	110	180			74	74	110
AGREGA BUNKERİ													
GÖZ ADEDİ	adet	4	3 - 4	4 - 4	4	4	4	2x3	4	4	4	4	4
GÖZ KAPASİTESİ	m3	6	15 - 15	20 - 20	30	30	40	30	10	10	25	25	25
TOPLAM KAPASİTE	m3	24	45 - 60	80 - 80	120	120	160	180	40	40	100	100	100
AGREGA TARTIM BANDI													
GENİŞLİK	mm	500	800	800	1000	1000	1000	1000	650	800	1000	1000	1000
UZUNLUK	mm	3000	10000	15350	15350	15350	15350	2x10000	9000	5500	15500	15500	15500
MOTOR GÜCÜ	kW	2,2	7,5	11	15	15	15	2x11	11	5,5	15	15	15
								22					
AGREGA TRANSFER BANDI													
GENİŞLİK	mm	KOVA	KOVA	800	KOVA	1000	1000	1200	TARTIM VE AKTARMA TEK BANTLA YAPILYOR	800	KOVA	1000	1000
UZUNLUK	mm		-	28000		28500	32000	34500		9000		13000	16500
MOTOR GÜCÜ	kW	2,2	7,5	22	30	30	37	75		11	30	22	30
KANTAR KAPASİTELERİ													
AGREGA TARTIM	kg	750	1000	2500	4000	4000	6000	9000	-	2500	4000	4000	6000
ÇİMENTO TARTIM	kg	150	300	500	1000	1000	2000	3000	500	500	1000	1000	2000
SU TARTIM	lt	70	150	300	700	700	1000	1250	300	300	700	700	1000
KATKI TARTIM	kg	20	50	50	50	50	50	50	50	50	50	50	50
ÇİMENTO HELEZONU													
ÇAP	mm	168	193	219	273	273	273	323	193	219	273	273	273
UZUNLUK	mm	10000	7500	11500	11500	11500	11500	12000	7500	11500	11500	11500	11500
MOTOR GÜCÜ	kW	7,5X2	7,5X2	11X2	15X2	15X2	15X2	18,5X2	7,5X2	11X2	15X2	15X2	15X2
		15	15	22	30	30	30	37					
ÇİMENTO SİLOSU													
KAPASİTE	ton	50	50	100	100	100	100	100	50	100	100	100	100
ÖNERİLEN ADET	Adet	1	1-2	2-4	2-4	2-4	2-4	4-6	1-2	2-4	2-4	2-4	2-4
KOMPRESÖR													
KAPASİTE	lt/dak.	800	1100	1880	1880	1880	2400	2400	1100	1100	1880	1880	2400
ÇALIŞMA BASINCI	bar	8	8	8	8	8	10	10	8	8	8	8	10
MOTOR GÜCÜ	kW	5,5	5,5	11	11	11	18,5	18,5	5,5	5,5	11	11	18,5
HİDRAFOR													
POMPA	m3/saat	10	15	30	50	50	50	2x50	15	15	25	25	50
ÇALIŞMA BASINCI	bar	5	5	5	5	5	5	5	5	5	5	5	5
DEPO HACMİ	lt	500	500	500	500	500	1000	2X1000	500	500	500	500	1000
MOTOR GÜCÜ	kW	5,5	5,5	11	18,5	18,5	18,5	2x18,5	5,5	5,5	11	11	18,5
								37					
TOPLAM MOTOR GÜÇLERİ													
STANDART 2 SİLOLU TESİS	kWh	40	60	120	180	180	230	375	60	110	185	175	230